

AX6033

4-slot ShoeBox Chassis



Front view



Interior view

Features

- Compact design for embedded applications
- Supports half-size SBC
- One 3.5" HDD drive bay and One slim CD-ROM drive; One internal 3.5" HDD drive bay
- Equipped with a 70W power supply
- Optional DC power module

System

Standard Color	Beige (PANTONE 414C)
Construction	Heavy-duty cold-rolled steel
Drive Capacity	Exposed 1 x 3.5" HDD drive bay and one slim CD-ROM drive; Internal 1 x 3.5" HDD drive bay
Cooling	1 x 80mm x 80mm ball-bearing fan (42.5CFM/each) with a removable filter
Front Panel Indicators	1 x power on/off; 1 x HDD
Rear Panel Controls	1 x power on/off; 1 x system reset
Pre-punched Rear Panel	2 x 9-pin; 1 x 25-pin; 2 x USB
System Board	Half-size SBCs
Expansion Interface	4-slot ISA or PCI backplane
Operating Temperature Range	0° C - 45° C (32° F - 113° F)
Dimensions	160mm (6.3") (W) x 275mm (10.8") (D) x 185mm (7.3") (H)
Weight (net/gross)	4.5 kg (9.92 lb)/5.7 kg (12.57 lb)

Ordering Information

AX6033WI/70 (with MOQ restriction)	With ATX6020/4, AT 70W power supply
AX6033WC/70 (with MOQ restriction)	With ATX6021/4, AT 70W power supply
AX6033WB/100 (with MOQ restriction)	With AT 100W power supply, w/o BP
AX-SLCD	Slim CD-ROM
AX-SLCDR	Slim CD-RW

* Specifications and certifications are limited to optional.

Power Supply Specifications

Item	Specifications		
	Input	Output	MTBF
AC AT 70W	AC 115/230V (Auto)	+5V @ 10A +12V @ 1.5A -12V @ 0.3A	100,000 hours
DC AT 72W	DC 36-72VDC	+5V @ 10A +12V @ 1.5A -12V @ 0.3A	100,000 hours
AC AT 100W	DC 115/230VDC (Auto)	+5V @ 15A +12V @ 12A -12V @ 0.5A	100,000 hours

Backplane Options

PICMG 1.0

Models	Slots per Segment (ISA/PCI/CPU)	Segment
ATX6020/4	4/0/0	Single
ATX6021/4	0/3/1	Single

Dimensions

