

OFP320

31.5" Full HD Digital Signage Display



Features

- Intel® Open Pluggable Specification (OPS)
- Pluggable engine box: Easy system configuration and maintenance (optional)
- Supports 2nd generation Intel® Core™/ Celeron® processor (OPS870 with Ivy Bridge or OPS860 with Sandy Bridge)
- Remote management: Intel® AMT 7.0 and AMT 8.0
- 31.5" TFT LCD - Full HD 1920 x 1080P



Specifications

LCD Panel	Size	31.5"
	Contrast	2500 : 1
	Pixel Pitch	363 x 363 (um)
	Viewing Angle (H/V)	178° x 178°
	Response Time	6.5ms
	Color	16.7M
	Brightness (cd/m ²)	450
	Board	CPU
Chipset		Intel® QM67 (OPS860) Intel® QM77 (OPS870)
Memory		1 x DDR3 SO-DIMM 1333 max. up to 4 GB
HDD		1 x 2.5" SATA HDD
Watchdog Timer		255 levels, 0-255 sec.
I/O	2 x USB 2.0 & 1 x VGA (OPS860) 2 x USB 2.0 & 1 x HDMI (OPS861) 2 x USB 3.0 & 1 x HDMI (OPS870)	
	Ethernet	1 x 10/100/1000Mbps Ethernet
	Expansion Slot	2 x PCI Express Mini Card (for optional wireless module)
Audio	Line-out/Mic-in	
Touchscreen	N/A	
Power Supply	450W, 100-240VAC	
Dimensions	781 mm (30.74") (W) x 118 mm (4.64") (D) x 471 mm (18.54") (H)	
	Packing Dimensions 970 mm (38.2") (W) x 260 mm (10.23") (D) x 620 mm (24.4") (H)	
Weight (net/gross)	27.1 kg (59.74 lb)/31.1 kg (68.56 lb)	
Environment	0 - +40° C, operation, 10% - 95% relative humidity	

Ordering Information

Standard	
OFP320	31.5" full HD digital signage display
Optional	
OPS870	Intel® OPS player (Ivy Bridge)
OPS861	Intel® OPS player with HDMI (Sandy Bridge)
OPS860	Intel® OPS player with VGA (Sandy Bridge)

* Specification and certifications are based on options and may vary.

Dimensions

