

OFP320

31.5" Full HD Digital Signage Display



Specifications

LCD Panel	Size	31.5"
	Contrast	2500 : 1
	Pixel Pitch	363 x 363 (um)
	Viewing Angle (H/V)	178° x 178°
	Response Time	6.5ms
	Color	16.7M
	Brightness (cd/m ²)	350
I/O	2 x USB 2.0 & 1 x VGA (OPS860/OPS860-HM) 2 x USB 2.0 & 1 x VGA (OPS830) 2 x USB 3.0 & 1 x HDMI (OPS870/OPS870-HM) 2 x USB 3.0 & 1 x HDMI (OPS885/OPS880/OPS880-HM) 3 x USB 3.0 , 1 x HDMI (OPS882-HM)	
Touchscreen	N/A	
Power Supply	450W, 100-240VAC	
Dimensions	781 mm (30.74") (W) x 118 mm (4.64") (D) x 471 mm (18.54") (H)	
Packing Dimensions	970 mm (38.2") (W) x 260 mm (10.23") (D) x 620 mm (24.4") (H)	
Weight (net/gross)	27.1 kg (59.74 lb)/31.1 kg (68.56 lb)	
Environment	0°C ~ +40°C (+32°F ~ +113°F), operation, 10% ~ 90% relative humidity	

Packing

- 1 x power cord
- 2 x screw

Features

- Open Pluggable Specification (OPS) compliance
- Pluggable engine box: Easy system configuration and maintenance (optional)
- 31.5" TFT LCD - Full HD 1920 x 1080P
- Supports VESA FPM PMI compliant flat panel mount

Ordering Information

Standard

OFP320	31.5" OPS compliance full HD digital signage display
--------	--

Optional

OPS870/OPS870-HM	OPS player with HDMI (Ivy Bridge)
OPS871/OPS871-HM	OPS player with HDMI (Ivy Bridge)
OPS860/OPS860-HM	OPS player with VGA (Sandy Bridge)
OPS830	OPS player with VGA (Intel® Cedar Trail)
OPS880/OPS880-HM	OPS player with HDMI (Haswell)
OPS885	OPS player with HDMI (Haswell)
OPS882-HM	OPS player with HDMI (Haswell)

* Specification and certifications are based on options and may vary.

Dimensions

